

SPEAKMAN® S-8829-CA-E

Sensorflo® AC Powered Lavatory Faucet

FEATURES:

- Above counter hot/cold mixer with built-in check valves and temperature limit stop.
- Ceramic manual override valve activates the faucet for continuous operation in the event of battery drain or user preference.
- Solenoid with built-in filter.
- Includes hoses needed to make mixer and manual override connections.
- Includes 8 in. deck plate.
- UL/CSA approved transformer 120 VAC to 12 DC with water proof connectors.
- Lead-free construction.
- Spout consists of all metal chassis and removable cover.
- Vandal resistant 60-second time out feature.
- Water conserving vandal-resistant flow control reduces flow to 0.5 gpm (1.89 L/min).
- NOTE: Stainless steel flexible supply hoses, 3/8 in. compression, to supply stops not included, see add-ons below.



COMPLIANCE:

- ASME A112.18.1/CSA B125.1 certified
- NSF 61 certified
- NSF 372 certified

FINISH:



PC

ADD-ONS:

- 0.5 gpm Boca spray outlet & 1.5 gpm laminar flow outlet kit A-BOLF
- Two (2) stainless steel flexible supply hoses to supply stops A-HS
- Under counter thermostatic mixing valve A-TMV
- Vandal-resistant screws for removable cover and custom wrench A-VRS
- 1.2 gpm laminar flow outlet A-ELF
- 1.2 gpm aerator A-EA12
- Tee with integral check valves A-TEE

OPTION: Add suffix to model

- Less transformer -LT

WARRANTY:

- 5 Year Limited

Architect/Engineer Approval Space:

SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: OCTOBER 2017

DIMENSIONS: NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.
 2. Inlet is 3/8" compression with male threads. Position faucet as close to the edge of the sink as possible.

