

## Kubos™ Hand Shower Wand

### MODELS:

- VS-3023: 2.5 GPM (9.5 L/min) flow rate
- VS-3023-E2: 2.0 GPM (7.6 L/min) flow rate
- VS-3023-E175: 1.75 GPM (6.6 L/min) flow rate

### FEATURES:

- 44 rubber spray outlets , 1 spray pattern
- Metal wand construction
- Shower wand has 1/2" -14 NPSM male inlet with check valve
- Bracket not included
- Includes 5' metal hose with (1) 1/2" -14 NPSM female inlet and (1) 1/2"-14 NPSM female outlet with check valve
- Corrosion resistant finishes
- Coordinates with Kubos Collection

### STOCK FINISHES:



PC BN MB

### SPECIALTY FINISHES:



BBZ BC ORB PB PN

### OPTIONS/ADD-ONS:

- VS-126: Wall mounted hand held shower bracket


### STANDARDS:

- ASME A112.18.1/CSA B125.1 certified

### WARRANTY:

Visit [www.speakman.com](http://www.speakman.com) for full product warranty information

- Limited Lifetime Warranty (consumer)
- 1 Year Limited Warranty (commercial)



All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

Architect/Engineer Approval Space:

P: 800-537-2107  
 F: 800-977-2747  
 W: WWW.SPEAKMAN.COM  
 R: 03-AUGUST 2021