

ANYSTREAM®



S-2251



S-2252



S-2252-1776



S-2253-AF

Showerheads GENERAL SPECIFICATION

Water conserving pressure compensating AUTOFLO® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ANSI A112.18.1M Standard. ½" NPT inlet.

□ S-2251

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 3-1/2" face. 8 Lexan deposit resisting plungers with 64 spray channels.

□ S-2252-AF

Polished chrome plated ANYSTREAM showerhead. Brass ball swivel joint. Brass shank. Spray adjusting T-handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.

□ S-2252-1776

Rough nickel plated Anystream® Liberty Bell showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.

□ S-2253-AF

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/4" face. 4 Lexan deposit resisting plungers with 32 spray channels.

OPTIONS

SUFFIX	DESCRIPTION
□ BB	Bright brass finish (S-2253-AF only)
□ BP	Blister pack packaging (S-2253-AF only)
□ BPT	1/2" British pipe thread inlet (not S-2252-1776)
□ ORB	Oil rubbed bronze (SD-02 and S-2251 only)
□ PN	Polished nickel finish (S-2251 only)
□ PVD	Polished brass finish (S-2251 only)
□ SC	Brushed chrome finish (S-2251 only)
□ SN	Brushed nickel finish (S-2251 only)
□ WGTPCBP	White with polished chrome trim (S-2253-AF)

This space for Architect/Engineer approval.

