

# SPEAKMAN COMPANY

## Alexandria ADA Hand-held Shower/Tub Combination With Grab/Slide Bar SM-6080-ADA-P

### DESCRIPTION

Speakman Alexandria ADA Hand-held Shower Combination unites the best products included in our Alexandria Series, while maintaining ADA requirements. The combination begins with our anti-scald balanced pressure valve with integral stops, featuring a brass body and adjustable temperature limit stop. The wall plate and handle are designed with definitive Alexandria Collection styling. Piston-type pressure balancing/ceramic regulating cartridge assembly with built-in check valves. Meets ASME A112.18.1 / CSA B125.1 & ASSE 1016 standards. The featured product in the Alexandria hand-held shower combination is the ANYSTREAM® VS-3011 hand shower with a 4" outer spray adjustment ring. Five self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. The center core nozzle delivers 12 massaging jets and a combination spray is included. Water-conserving pressure compensating AUTOFLO® device reduces flow to 2.5 GPM / 9.46 LPM maximum, to meet existing ANSI A112.18.1 Standard. To control the water supply between the brass S-2500 shower arm and your VS-3011 is the VS-156 ADA compliant volume control. The adjustability of your VS-153 grab/slide bar will allow you to choose the perfect height to rest your hand shower, while still meeting ADA standards

### SPECIFICATIONS

SM-6000-P Anti-Scald Balanced Pressure Valve:

Connections: 1/2" female copper sweat inlets  
& shower outlet; 1/2" NPT female  
tub outlet

Flow Rate: For use with showerheads rated at  
2.0 GPM (7.6 LPM) or higher.

VS-3011 Hand-Held Shower:

Supply: 1/2" NPT female  
Flow Rate: 2.5 GPM / 9.46 LPM MAX

S-2500 Shower Arm:

Supply: 1/2" NPT male inlet  
Outlet: 1/2" NPT male outlet

VS-156 Volume Control:

Supply: 1/2" NPSM male inlet  
Outlet: 1/2" NPSM female outlet

### INSTRUCTIONS

See individual products for installation of the  
components and warranty information.

### ROUGH-IN

92-3460

