

# FV6 & DV6


## LIGHT COMMERCIAL COIN DROP FRONT CONTROL FRONT LOAD WASHER & MATCHING DRYER

### Built for Reliable Performance

Engineered and built like no other, the Speed Queen® coin drop front load washer and dryer are designed for performance and reliability. Our commercial-grade construction is rugged, dependable, and built to last. Plus, property owners can rely on the practical ingenuity of features designed to make their lives simpler and more productive.



FV6 Control Panel



DV6 Control Panel

### Washer:

- Revolutionary balancing technology redistributes and balances even the most unbalanced loads
- Increased 440 G-Force extraction speed reduces drying times
- Durably designed to deliver long-lasting performance with features like a rugged suspension system, stainless steel wash tub and dynamic balancing system
- ADA Compliant

### Dryer:

- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Efficient and fast dry cycle



# LIGHT COMMERCIAL COIN DROP FRONT CONTROL FRONT LOAD WASHER & MATCHING DRYER



**FV6**



**DV6**

Product Code	FV6010WN
Color	White
Capacity - lb (kg)	21 (9.5)
Cylinder Volume - cu.ft. (liters)	3.42 (96.8)
Spin Speed G-Force (RPM)	440 (1200)
Motor Size - HP (kw)	0.9 (0.67)
Water Consumption Per Cycle - g (liter)*	13.68 (51.8)
IWF (Water Factor) - gal/ft <sup>3</sup> (liters/liter/cycle)*	4.0 (0.53)
MEF <sub>J2</sub> (Modified Energy Factor) ft <sup>3</sup> /kWh/cycle (Liters/kWh/cycle)*	2.20 (62.3)
Available Water Temperatures	Cold, Warm, Hot
Available Cycles	Normal, Synthetic, Delicate
Electrical Requirements (v/Hz/Ph-Amp)	120/60/1 - 15 Amp
Water Pressure - p.s.i (bar)	20-120 (1.4/8.3)
Drain	Pump, Gravity
Cylinder Finish	Stainless Steel
Net Weight - lb (kg)	260 (118)
Shipping Weight - lb (kg)	270 (122.2)
Shipping Dimensions	Width 34 Depth 30 Height 44.5
Agency Approvals	cULus, ENERGY STAR® certified
Model No.	SFNNCASP116TW01

Product Code	Gas: DV6010WG Electric: DV6010WE
Color	White
Capacity - lb (kg)	18 (8.2)
Cylinder Volume - cu.ft. (liters)	7.0 (198)
Motor (Thermal Protected)	0.33 HP
Type of Gas (Gas Models Only)	Factory Equipped Natural
Air Outlet Diameter - in	4
Exhaust Airflow - cfm (liters/sec)	220 (105)
Available Cycles	High, Medium, Low, Delicates, No Heat
Electrical Requirements	**Electric 120/208/240/60/1-30 Amp Gas 120/60/1-15 Amp
Heating Element	Electric 5350W, 240V / 4750W, 208V Gas 25,000 Btu
Net Weight - lb (kg)	150 (68)
Shipping Weight - lb (kg)	161 (73)
Shipping Dimensions	Width 30.5 Depth 29.5 Height 45
Agency Approvals	cULus
Model No.	SDENCAGS176TW01 SDGNCAGS116TW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
<b>FV6010WN</b>	26.875	44.34	31.36	14.6***	24
<b>DV6010WE/DV6010WG</b>	26.875	44.34	28	15.44	23.5

**Required Coin Kits** (sold separately)

Coin Box – Model #: CK043

**For Commercial Use Only**

Supply inject kits available.

\* Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

\*\* Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V..

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

\*\*\* For ADA compliance turn legs out from base 0.5 inches

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

AR22-0037

Speed Queen by Alliance Laundry Systems