

Valton™ Single-handle kitchen sink faucet with sidespray 24278

Features

- 8-11/16" (220 mm) spout reach.
- 1.5 gpm (5.7 lpm) maximum flow rate at 60 psi (4.14 bar).
- Single lever handle makes adjusting water temperature easy.
- Temperature memory allows faucet to be turned on and off at the temperature set during prior usage.
- Matching sidespray provides flexibility and convenience for cleaning and food prep.
- KOHLER ceramic disc valves exceed industry longevity standards for a lifetime of durable performance.

Material

- Premium metal construction for durability and reliability.
- Durable STERLING finishes built to resist corrosion.

Installation

- Two-hole or four-hole installation (escutcheon plate included).
- Flexible supply lines simplify installation.


Adapters, Rough-in and Extension Kits

1327990

Range: 2-1/2" (64 mm) -4-5/8" (117 mm)

Included Components

Additional Components: Escutcheon plate



ADA CSA B651

Codes/Standards

ASME A112.18.1/CSA B125.1 NSF/ANSI 61 NSF/ANSI 372 All applicable US Federal and State material regulations DOE - Energy Policy Act 1992 California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651

STERLING[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description




CP Polished Chrome

Valton™

Single-handle kitchen sink faucet with sidespray 24278





Technical Information

All product dimensions are nominal.

Drain included: No

Spout:

Spout reach: 8-11/16" (220 mm)

Notes

Install this product according to the installation instructions.

ADA complaint for faucet handles only.

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.