

CK & CKT 15 E, CK Trend Technical Data

Technical Data



Certified to ANSI/UL Std. 2021
Conforms to CAN/CSA Std. 22.2 No. 46



Model	CK 15 E	CKT 15 E	CK 150-1 Trend	CK 200-2 Trend
Item number	074058	230345	236304	236305
Voltage	120 V	120 V	120 V	240 V or 208 V
Wattage	1500 W	1500 W	1500 W	2000 W 1800 W
Amperage	12.5 A	12.5 A	12.5 A	8.3 A 8.7 A
Rated output Btu/hr	5118	5118	5118	6824 6142
Air volume	106 CFM	106 CFM	70.6 CFM	70.6 CFM
Recommended circuit breaker size ¹	15 A	15 A	15 A	15 A
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG	14 AWG
Timer	no	yes	N/A	N/A
Room size estimate	150 sq.ft.	150 sq.ft.	150 sq.ft.	200 sq.ft.
Heating element	nichrome wire		ceramic positive temperature coefficient (PTC)	
Thermostat & high limit	bimetal type		bimetal type	
Motor	18 W shaded pole		20 W shaded pole	
Blower	galvanized steel, squirrel cage type		glass-reinforced polycarbonate, radial type	
Dimensions	H 18 ¹ / ₈ " (460 mm) x W 13 ³ / ₁₆ " (335 mm) x D 4 ³ / ₁₆ " (123 mm)		H 15 ³ / ₄ " (400 mm) x W 10 ⁷ / ₈ " (275 mm) x D 5 ¹ / ₈ " (131 mm)	
Weight	8.0 lb (4.4 kg)		5.5 lb (2.5 kg)	
Temperature range	41-86 °F (5-30 °C)		45-95 °F (7-35 °C)	
Frost protection setting	45 °F (7 °C)		45 °F (7 °C)	
Operating noise	49.7 dB(a)		49.0 dB(a)	

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary.