



SBC635MBIIFTWIN



33.5" x 24" x 25.88" (H x W x D)

Built-in residential beer dispenser, auto defrost with digital thermostat, dual tap system, panel-ready door, and black cabinet

Highlights:

Dual tap system allows you to serve beer from two 1/6 kegs

Designed for built-in installation under the counter

Customizable door front accepts full overlay panels for a seamless look that can blend into cabinetry

Product Features:

| | |
|---------------------------|---|
| Full-sized beer dispenser | Large 5.6 cu.ft. interior can accept a full half barrel keg, two 1/6 barrel kegs, or a pony keg |
| Built-in capable | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require extra space due to the door design. Width should be 25" to 25 1/4". For more information, see the user manual |
| Dual tap system | Twin taps let you serve two different types of beer from two 1/6 sized (sixtel) kegs |
| Tap Kit | Includes a 5 lb. CO2 tank and regulator, draft arm, Sankey American tap, and connection hardware |
| Panel-ready door | Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the door or blend it into your cabinetry design (panel dimensions: 23 3/4" W x 30 13/16" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |
| Ideal beer temperature | Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature |
| Automatic defrost | Reduced user maintenance with auto defrost operation |

Full finished black cabinet, Allows the beer dispenser to be used freestanding



SBC635MBIIFTWIN Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 33.5" (85 cm) |
| Width | 24.0" (61 cm) |
| Width with Door Open | 25.25" (64 cm) |
| Depth | 25.88" (66 cm) |
| Depth with door at 90° | 47.5" (121 cm) |
| Capacity | 5.6 cu.ft. (159 L) |
| Defrost Type | Automatic |
| Door | Panel-Ready |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Energy Usage/Year | 310.0kWh/year |
| Amps | 0.86 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 100.0 lbs. (45 kg) |
| Shipping Weight | 105.0 lbs. (48 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Tap Kit | Yes |
| Number of Taps | 2 |
| Thermostat Type | Digital |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.13 oz. |
| High Side PSI | 250.0 |
| Low Side PSI | 110.0 |
| Inter Height | 28.0" (71 cm) |
| Interior Width | 20.5" (52 cm) |
| Interior Depth | 19.0" (48 cm) |
| Compressor Step Height | 8.25" (21 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 33° to 50° F |

