## SUMMIT

# **SEH4630SS**



#### 29.5" x 29.5" x 19.69" (H x W x D)

30" wide European style convertible wall-mounted range hood in stainless steel

#### **Highlights:**

30" wide wall-mounted range hood

Versatile design for ducted or recirculating operation with a set of carbon filters included

Pre-installed 3-prong plug for fast setup

#### **Product Features:**

30" wide wall-mounted range hood	European style range hood designed to bring effective ventilation over 30" wide cooking surfaces	
Convertible design with no additional purchase necessary	Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible	
Charcoal filter set included	Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode	
Powerful ventilation	400 CFM blower to effectively remove smoke and cooking odors from your kitchen	
Cord included	Pre-installed power cord with 3-prong plug for 115V outlets	
LED lighting (bulbs included)	Includes two pre-installed LED bulbs to illuminate your cooking surface	
Adjustable height	Includes a telescoping chimney extender that allows you to adjust the overall height between 25 1/4" to 37"	
Stainless steel finish	Durable construction in an attractive style with a horizontal grain	
Intuitive controls	Touch buttons located towards the front of the hood let you adjust your ventilation and lighting as needed	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



## SUMMIT

#### SEH4630SS Specifications:

Height of Cabinet29.5" (75 cm)Width29.5" (75 cm)Depth19.69" (50 cm)DoorStainless SteelUS Electrical SafetyETLVoltage/Frequency115 V AC/60 HzWeight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Duct Shape6" Round	Overview		
Depth19.69" (50 cm)DoorStainless SteelUS Electrical SafetyETLVoltage/Frequency115 V AC/60 HzWeight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Height of Cabinet	29.5" (75 cm)	
DoorStainless SteelUS Electrical SafetyETLVoltage/Frequency115 V AC/60 HzWeight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Width	29.5" (75 cm)	
US Electrical SafetyETLVoltage/Frequency115 V AC/60 HzWeight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Depth	19.69" (50 cm)	
Voltage/Frequency115 V AC/60 HzWeight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Door	Stainless Steel	
Weight52.0 lbs. (24 kg)Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	US Electrical Safety	ETL	
Shipping Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086835Range HoodInstallationInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Voltage/Frequency	115 V AC/60 Hz	
Parts & Labor Warranty1 YearUPC761101086835Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Weight	52.0 lbs. (24 kg)	
UPC761101086835Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Shipping Weight	55.0 lbs. (25 kg)	
Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Parts & Labor Warranty	1 Year	
InstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	UPC	761101086835	
VentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Range Hood		
ControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Installation	Wall-Mounted	
LightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting	Convertible	
Number of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Controls	Push Button	
Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Light	Yes	
Number of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Number of Lights	2	
Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Light Type	LED	
Sone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Number of Fan Speeds	3	
Minimum Height 15.75" (40 cm)   Maximum Height 29.5" (75 cm)	Maximum Air Movement	400.0 CFM	
Maximum Height 29.5" (75 cm)	Sone Rating	10	
	Minimum Height	15.75" (40 cm)	
Duct Shape 6" Round	Maximum Height	29.5" (75 cm)	
	Duct Shape	6" Round	

### 2 Charcoal Filters Included for Recirculating Use



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

