

SCR215L



20.88" x 17" x 18.75" (H x W x D)

Commercially approved glass door refrigerator with digital thermostat and white cabinet finish

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Stainless steel trimmed glass door provides a full view of stored items

Digital thermostat with convenient external location for easy temperature control

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Double pane tempered glass door	Heat resistant design provides clear view of stored products, with an elegant trim in stainless steel
Automatic defrost	No-frost convenience for reduced user maintenance
Digital thermostat	Electronic controls offer more precision in temperature management, with a readout viewable in Celsius or Fahrenheit
Factory installed lock	Keyed lock for a secure interior
LED lighting	Interior LED lighting offers an energy efficient view in an attractive blue hue
Adjustable chrome shelves	Rearrange the refrigerator space to fit any sized item or remove shelves for simple cleanup
Sealed back	Space-saving design with no exposed coils in the rear offers easy cleanability
Professional handle	Stainless steel handle offers a solid grip and professional look



SCR215L Specifications:

Overview	
Height of Cabinet	20.25" (51 cm)
Height to Hinge Cap	20.88" (53 cm)
Width	17.0" (43 cm)
Depth	18.75" (48 cm)
Depth with Handle	20.38" (52 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.7 cu.ft. (48 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	55.0 lbs. (25 kg)
Shipping Weight	60.0 lbs. (27 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	RHD
Reversible	No
Shelf Type	Chrome
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Refrigerant Type	R600a
Refrigerant Amount	0.89oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs Qty	2
Interior Light	Yes
Temperature Range	34°F to 43°F
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	13.75" (35 cm)
Interior Depth	15.0" (38 cm)
Compressor Step Height	8.0" (20 cm)

Compressor Step Width	13.75" (35 cm)
Compressor Step Depth	6.0" (15 cm)

