## SUMMIT

# **FF1843BIF**



34.25" x 17.75" x 24" (H x W x D)

18" wide built-in undercounter all-refrigerator with a panelready door, and digital thermostat

#### **Highlights:**

Just under 18" wide for an easy fit, with a flush back design to save space

Flexible design allows built-in or freestanding use

Digital thermostat offers precise and convenient temperature control

#### **Product Features:**

| Commercially approved     | ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments   |  |
|---------------------------|--|--|
| Built-in capable          | Front-breathing design lets you make the best use of space by installing your appliance under the counter  |  |
| Integrated door frame     | Stainless steel door frame accepts full overlay panels for users to create a seamless custom look (panel size: 17 1/2" W x 27 3/4" H; maximum weight: 10 lbs.) |  |
| Automatic defrost         | Reduced maintenance with auto defrost system   |  |
| Digital thermostat        | Electronic controls for precise temperature management.  |  |
| Digital display           | Temperature readout can be shown in Celsius or Fahrenheit  |  |
| LED lighting              | Automatically illuminates when the door is open  |  |
| Adjustable chrome shelves | Rearrange interior space to accommodate all sizes or remove shelves for simple cleanup   |  |
| Flush back                | Space saving design  |  |







### FF1843BIF Specifications:

| Height of Cabinet 34.25" (87 cm)  Width 17.75" (45 cm)  Width with Door Open 18.63" (47 cm)  Depth 24.0" (61 cm)  Depth with door at 90° 40.0" (102 cm)  Capacity 2.7 cu.ft. (76 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety |  |  |  |
|--|--|--|--|
| Width with Door Open 18.63" (47 cm)  Depth 24.0" (61 cm)  Depth with door at 90° 40.0" (102 cm)  Capacity 2.7 cu.ft. (76 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical ETL-C  |  |  |  |
| Depth 24.0" (61 cm)  Depth with door at 90° 40.0" (102 cm)  Capacity 2.7 cu.ft. (76 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical ETL-C   |  |  |  |
| Depth with door at 90° 40.0" (102 cm)  Capacity 2.7 cu.ft. (76 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical ETL-C  |  |  |  |
| Capacity 2.7 cu.ft. (76 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical ETL-C   |  |  |  |
| Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical ETL-C   |  |  |  |
| DoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian ElectricalETL-C   |  |  |  |
| Cabinet Black US Electrical Safety ETL Canadian Electrical ETL-C   |  |  |  |
| US Electrical Safety ETL  Canadian Electrical ETL-C  |  |  |  |
| Canadian Electrical ETL-C  |  |  |  |
|  |  |  |  |
|  |  |  |  |
| Sanitation ETL-S   |  |  |  |
| Energy Usage/Year 250.0kWh/year  |  |  |  |
| Amps 1.1   |  |  |  |
| Voltage/Frequency 115 V AC/60 Hz   |  |  |  |
| Weight 90.0 lbs. (41 kg)   |  |  |  |
| Shipping Weight 109.0 lbs. (49 kg)   |  |  |  |
| Parts & Labor Warranty 1 Year  |  |  |  |
| Compressor Warranty 5 Years  |  |  |  |
| UPC 761101047003   |  |  |  |
| Refrigerator Features  |  |  |  |
| Door Swing RHD   |  |  |  |
| Reversible Factory Reversible  |  |  |  |
| Shelf Type Chrome  |  |  |  |
| Shelf Qty 4  |  |  |  |
| Adjustable Shelves Yes   |  |  |  |
| Thermostat Type Digital  |  |  |  |
| Fan Type Interior and Exterior   |  |  |  |
| Refrigerant Type R600a   |  |  |  |
| Refrigerant Amount 1.06oz.   |  |  |  |
| High Side PSI 150.0  |  |  |  |
| Low Side PSI 50.0  |  |  |  |
| Level Legs Qty 2   |  |  |  |
| Interior Light Yes   |  |  |  |
| Sound Level 33.1 dB  |  |  |  |
| Dimensions   |  |  |  |
| Interior Height 23.5" (60 cm)  |  |  |  |

| Interior Width         | 12.75" (32 cm) |
|------------------------|----------------|
| Interior Depth         | 16.75" (43 cm) |
| Compressor Step Height | 4.5" (11 cm)   |
| Compressor Step Width  | 12.75" (32 cm) |
| Compressor Step Depth  | 4.5" (11 cm)   |

