accuc@ld

ARG61PVBIADA



31.75" x 23.38" x 25" (H x W x D)

Performance series Pharma-Vac 6 cu.ft. ADA height glass door commercial all-refrigerator for the display and refrigeration of vaccines; designed for recessed or freestanding installation

Highlights:

Sized just under 32" high to fit under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines	
ADA Compliant	Just under 32" tall designed to fit under ADA compliant counters	
Recessed installation capable	Versatile design allows recessed installation under counters or freestanding use	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Commercial design	Meets UL-471 commercial standards	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2°C to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	



accuc@ld

ARG61PVBIADA Specifications:

Overview		
Nominal Height	32.0" (81 cm)	
Height of Cabinet	31.75" (81 cm)	
Nominal Width	24.0" (61 cm)	
Width	23.38" (59 cm)	
Width with Door Open	23.88" (61 cm)	
Nominal Depth	25.0" (64 cm)	
Depth	25.0" (64 cm)	
Depth with Handle	26.75" (68 cm)	
Depth with door at 90°	47.0" (119 cm)	
Capacity	6.0 cu.ft. (170 L)	
Defrost Type	Automatic	
Door	Glass	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	0.75	
Voltage/Frequency	115 V AC/60 Hz	
Weight	125.0 lbs. (57 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101075303	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wire	
Shelf Qty	4	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	1.66oz.	
High Side PSI	280.0	
Low Side PSI	90.0	
Interior Light	Yes	
Temperature Range	2°C to 8°C	
Dimensions		
Interior Height	24.5" (62 cm)	

Interior Width	20.0" (51 cm)
Interior Depth	17.0" (43 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.0" (13 cm)



