accuceld

AFZ1PVMC



22.25" x 18.5" x 23.25" (H x W x D)

Performance Series 1.4 cu.ft. MOMCUBE breast milk freezer

Highlights:

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Designed for storing breast milk in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Intelligent microprocessor digital temperature controller

Product Features:

MOMCUBE Breast Milk Freezer	Purpose-built Performance Series freezer for the long-term storage of breast milk
Purpose-built design	Designed and purpose-built for breast milk storage in accordance with the CDC's guidelines
+/-1ºC Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between -18°F to -4ºF
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Manual defrost operation	Static cooling system for an efficient and stable interior
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Open door alarm	Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com \checkmark



accucold

AFZ1PVMC Specifications:

Overview	
Height of Cabinet	22.25" (57 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	73.0 lbs. (33 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106915
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	16.5" (42 cm)
Interior Width	15.25" (39 cm)
Interior Depth	15.75" (40 cm)
	()
Shelf Type	Wire
Shelf Type Shelf Qty	
	Wire
Shelf Qty	Wire 2
Shelf Qty Adjustable Shelves	Wire 2 Yes
Shelf Qty Adjustable Shelves Thermostat Type	Wire 2 Yes Digital
Shelf Qty Adjustable Shelves Thermostat Type Interior Light	Wire 2 Yes Digital Yes
Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type	Wire 2 Yes Digital Yes R290a
Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount	Wire 2 Yes Digital Yes R290a 0.85 oz.
Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI	Wire 2 Yes Digital Yes R290a 0.85 oz. 280.0
Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Wire 2 Yes Digital Yes R290a 0.85 oz. 280.0 130.0
Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Compressor Step Height	Wire 2 Yes Digital Yes R290a 0.85 oz. 280.0 130.0 8.25" (21 cm)



