SUMMIT

HC20SSADA



5.5" x 20" x 20" (H x W x D)

20 inch wide ADA compliant under cabinet convertible range hood for ducted or ductless use in stainless steel, made in North America with a remote wall switch

Highlights:

ADA compliant design allows you to control the hood from a wall light switch for easier accessibility

20 inch wide pairs well with a variety of ranges and cooktops

Made in North America in a TAA designated country

Product Features:

20" Wide ADA Compliant Range Hood	Convertible hood designed for ducted or ductless installation in compliant with ADA guidelines
ADA compliant design	Hood is wired to run off a wall switch for improved accessibility, with a remote terminal block included
Under cabinet range hood	Low profile design offers classic style to finish your kitchen
20 inch width	Sized for use over 20 inch cooking surfaces (additional sizes available)
Convertible design	Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible
Stainless steel finish	Real stainless steel with a horizontal grain for a clean, professional look
Easy conversion	Ships pre-set for recirculating mode but can be converted in a few simple steps
Versatile top or rear exhaust	Can be connected to 3 1/4" x 10" vertical or horizontal exterior venting or 7" round vertical (transition required for both)
Powerful ventilation	Can operate at 270 CFM to ensure thorough ventilation of your cooking surface

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com \checkmark



SUMMIT

HC20SSADA Specifications:

Overview		
Height of Cabinet	5.5" (14 cm)	
Width	20.0" (51 cm)	
Depth	20.0" (51 cm)	
Cabinet	Stainless Steel	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	1.7	
Voltage/Frequency	115 V AC/60 Hz	
Weight	11.0 lbs. (5 kg)	
Parts & Labor Warranty	1 Year	
UPC	761101107202	
Range Hood		
Installation	Under Cabinet	
Venting	Convertible	
Controls	Dial	
Number of Fan Speeds	2	
Maximum Air Movement	270.0 CFM	
Sone Rating	6	
Duct Shape	3"1/4" x 10" rectangular or 7" round	



