

# SBC7BRSCM2LHD



#### 33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew/nitro coffee dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes adjustable legs and caster set for optional mobility

#### **Highlights:**

Made in Europe

Dual tap system lets you serve both regular cold brew and nitro coffee

Designed for recessed installation or portable use with a caster set included

### **Product Features:**

24" Wide Cold Brew/Nitro Coffee Dispenser	Kegerator includes all of the equipment you need to serve cold brew and nitro coffee from two sixtel or Cornelius kegs	
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA	
Versatile use	Approved for both residential and commercial settings	
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Dispenses both flat and nitro coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts	
Complete dual tap coffee kit	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Slim counter height dimensions for recessed or freestanding use	I Ideal 24" footprint for an easy fit	
Height adjustable	Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





## SBC7BRSCM2LHD Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	22.38" (57 cm)
Depth with Handle	24.0" (61 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106267
UPC Kegerator	761101106267
	761101106267
Kegerator	
Kegerator Door Swing	LHD
Kegerator   Door Swing   Reversible	LHD
Kegerator     Door Swing     Reversible     Height Adjustable	LHD No Yes
Kegerator     Door Swing     Reversible     Height Adjustable     Tap Kit	LHD No Yes Yes
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of Taps	LHD No Yes Yes 2
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable Shelves	LHD No Yes Yes 2 Yes Glass and
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf Type	LHD No Yes Yes 2 Yes Glass and Scalloped
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf Qty	LHD No Yes Yes 2 Yes Glass and Scalloped 4
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf QtyThermostat Type	LHD No Yes Yes 2 Yes Glass and Scalloped 4 Dial
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf QtyThermostat TypeInterior Light	LHD No Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf QtyThermostat TypeInterior LightRefrigerant	LHD No Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes R600a
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf QtyThermostat TypeInterior LightRefrigerant Amount	LHD No Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes R600a 0.64 oz.
KegeratorDoor SwingReversibleHeight AdjustableTap KitNumber of TapsAdjustable ShelvesShelf TypeShelf QtyThermostat TypeInterior LightRefrigerant AmountInter Height	LHD No Yes Yes Class and Scalloped Class and Scalloped 4 Dial Yes R600a 0.64 oz. 27.75" (70 cm)

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F



