

SBC7BRSNCF2LHD



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved nitro coffee dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes adjustable legs and caster set for optional mobility

Highlights:

Made in Europe

Dual tap system lets you serve from two sixtel kegs

Designed for recessed installation or portable use with a caster set included

Product Features:

24" Wide Nitro Coffee Dispenser	Kegerator includes all of the equipment you need to serve nitro coffee from two sixtel kegs	
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA	
Versatile use	Approved for both residential and commercial settings	
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Complete dual tap nitro coffee kit	Commercial grade tap kit includes a dual tap stainless steel stout style draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Slim counter height dimensions for recessed or freestanding use	d Ideal 24" footprint for an easy fit	
Height adjustable	Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter	
Leg shield included	Removable cover that lets you fill the gap that can appear between the refrigerator's kickplate and floor when raising the height	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 \checkmark





SBC7BRSNCF2LHD Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	22.38" (57 cm)
Depth with Handle	24.0" (61 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106250
Kegerator	
Kegerator Door Swing	LHD
-	
Door Swing	LHD
Door Swing Reversible	LHD Yes
Door Swing Reversible Height Adjustable	LHD Yes Yes
Door Swing Reversible Height Adjustable Tap Kit	LHD Yes Yes Yes
Door Swing Reversible Height Adjustable Tap Kit Number of Taps	LHD Yes Yes Yes 2
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves	LHD Yes Yes Yes 2 Yes Glass and
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type	LHD Yes Yes Yes 2 Yes Glass and Scalloped
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty	LHD Yes Yes Yes 2 Yes Glass and Scalloped 4
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type	LHD Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light	LHD Yes Yes Yes Class and Scalloped 4 Dial Yes
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant	LHD Yes Yes Yes Class and Scalloped 4 Dial Yes R600a
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant Amount	LHD Yes Yes Yes Class and Scalloped 4 Dial Yes R600a 0.64 oz.
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant Amount Inter Height	LHD Yes Yes Yes Class and Scalloped 4 Dial Yes R600a 0.64 oz. 27.75" (70 cm)

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F



