SUMMIT

SEH3624SSADA



37" x 23.56" x 19.69" (H x W x D)

24" wide ADA-compliant European-style convertible wallmounted range hood in stainless steel with remote wall switch

Highlights:

ADA-compliant design allows you to control the hood from a wall light switch for easier accessibility

24" wide range hood ideal for apartments and other smaller kitchen spaces

Versatile design for ducted or recirculating operation with a set of carbon filters included

Product Features:

| 24" wide wall-mounted range hood | European style range hood designed to bring effective ventilation over 24" wide cooking surfaces |
|--|--|
| ADA-compliant design | Control panel comes on a remote terminal block to be installed according to ADA compliant guidelines for improved accessibility (some assembly required) |
| Convertible design with no additional purchase necessary | Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible |
| Charcoal filter set included | Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode |
| Powerful ventilation | 400 CFM blower to effectively remove smoke and cooking odors from your kitchen |
| Cord included | Pre-installed power cord with 3-prong plug for 115V outlets |
| LED lighting (bulbs included) | Includes two pre-installed LED bulbs to illuminate your cooking surface |
| Adjustable height | Includes a telescoping chimney extender that allows you to adjust the overall height between 25 1/4" to 37" |
| Stainless steel finish | Durable construction in an attractive style with a horizontal grain |





SEH3624SSADA Specifications:

| Overview | |
|--|-----------------------------------|
| Height of Cabinet | 37.0" (94 cm) |
| Width | 23.56" (60 cm) |
| Depth | 19.69" (50 cm) |
| Door | Stainless Steel |
| US Electrical Safety | ETL |
| Amps | 2.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 43.0 lbs. (20 kg) |
| Parts & Labor Warranty | 1 Year |
| UPC | 761101107288 |
| Range Hood | |
| Installation | Wall-Mounted |
| Manting | 0 |
| Venting | Convertible |
| Controls | Push Button |
| | |
| Controls | Push Button |
| Controls Light | Push Button Yes |
| Controls Light Number of Lights | Push Button Yes 2 |
| Controls Light Number of Lights Light Type | Push Button Yes 2 LED |
| Controls Light Number of Lights Light Type Number of Fan Speeds | Push Button Yes 2 LED |
| Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement | Push Button Yes 2 LED 3 400.0 CFM |
| Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement Sone Rating | Push Button Yes 2 LED 3 400.0 CFM |



