## accucold

# AFS14PVDL2B



#### 74.38" x 23.5" x 25.25" (H x W x D)

Performance series Pharma-Vac 9.53 cu. ft. upright frostfree vaccine all-freezer with a NIST calibrated temperature logger (DDL)

#### **Highlights:**

NIST calibrated DDL included for accurate temperature logging

Designed and purpose built to meet demanding needs of life science, vaccine, laboratory and medical cold storage applications

Intelligent microprocessor digital temperature controller

### **Product Features:**

24" Wide Upright All-Freezer	24" Wide upright Performance Series vaccine all-freezer designed for healthcare settings	
Performance Series freezer	Purpose-built all-freezer for vaccine storage in medical, pharmaceutical, and life science applications	
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines	
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additiona information on this logger's features, view the DL2BKit on our website	
Spacious capacity	Over 9.5 cu.ft. of storage inside	
Frost-free operation	No-frost operation for minimal user maintenance	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC senso in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management	

Adiuntable temperature between -30°C to -10°C

# accuceld

## AFS14PVDL2B Specifications:

Overview			
Nominal Height	75.0" (191 cm)		
Height of Cabinet	74.38" (189 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.5" (60 cm)		
Width with Door Open	23.75" (60 cm)		
Nominal Depth	26.0" (66 cm)		
Depth	25.25" (64 cm)		
Depth with Handle	26.75" (68 cm)		
Depth with door at 90°	49.38" (125 cm)		
Capacity	9.53 cu.ft. (270 L)		
Defrost Type	Frost-Free		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	4.3		
Voltage/Frequency	115 V AC/60 Hz		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101152196		
Freezer			
Door Swing	RHD		
Reversible	Factory Reversible		
Interior Height	43.75" (111 cm)		
Interior Width	15.25" (39 cm)		
Interior Depth	16.5" (42 cm)		
Shelf Type	Wire		
Shelf Qty	6		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Interior Light	Yes		
Fan Type	Interior		
Refrigerant Type	R290a		
Refrigerant Amount	3.27 oz.		
High Side PSI	280.0		
Low Side PSI	130.0		

Compressor Step Height	10.0" (25 cm)
Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	15.25" (39 cm)
Temperature Range	-30 to -10°C



