

Location:



Tub-Shower & Hand Shower System 3506-H321-V-CYL-B

Specification Submittal



Feature Highlights

- Symmons Tub-Shower & Hand Shower System with lever handles
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon
- Separate triple outlet diverter valve with lever handle
- Showerhead #352SH, single mode, 3 inch diameter
- Showerhead mounting bracket and flange
- Wall/hand shower #H321-V, single mode with 5 foot flexible metal hose, in-line vacuum breaker, wall connection
- 30 inch slide bar and cradle for hand shower mounting
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available
- Tub spout, #067
- Polished chrome finish (standard)

Model Numbers

- 3506-H321-V-CYL-B
Tub-Shower and Hand Shower System with Symmons Temptrol® mixing valve, p/n 4000-BODY and triple outlet diverter, p/n 4-460E-BODY
- 3506-H321-V-CYL-B-TRM
Trim only, valve and diverter ordered separately
- 4000-BODY
Symmons Temptrol® mixing valve without trim
- 4000-X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service
- 4-460E-BODY
Symmons triple outlet diverter valve without trim

Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
 - Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n 4000-X-BODY
(Option only applies when ordering model 3506-H321-V-CYL-B)
- REV Reverse coring in valve for back to back installations; hot on right, cold on left,
(only available with -X integral service stops)
- 2.0 2.0 gpm (7.6 L/min) flow rate restrictor
- 1.5 1.5 gpm (5.7 L/min) flow rate restrictor
- 352SH-3 Showerhead is three-mode in place of standard single mode
- L/HD Showerhead not included
(includes showerhead arm and flange only)
- L/HS Hand Shower wand not included
(includes hose, in-line vacuum breaker, wall connections and flange only)
- 72 6 foot flexible metal hose in place of 5 foot
- R60 5 foot vinyl hose in place of flexible metal hose
- R72 6 foot vinyl hose in place of flexible metal hose
- QD Quick-disconnect at hand shower wall connection
- SS Slip-on type tub spout

Standards / Certifications

ASME A112.18.1-2005 / CSA B125.1-05

Americans with Disabilities Act (ADA) compliant

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions Dia Tub-Shower & Hand Shower System, 3506-H321-V-CYL-B

