


Location:



# Duro™ Shower-Hand Shower System 3605-H321-V Specification Submittal



## Feature Highlights

- Symmons Shower-Hand Shower System with lever handles
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon
- Separate dual outlet diverter valve with lever handle
- Showerhead #362SH, single mode, 3 inch diameter
- Showerhead mounting bracket and flange
- Wall/hand shower #H321-V, single mode with 5 foot flexible metal hose, in-line vacuum breaker, wall connection
- 30 inch slide bar and cradle for hand shower mounting
- Standard flow rate is 2.5 gpm (9.5 L/min)  
*Optional lower flow rate restrictor available* 
- Polished chrome finish (standard)

## Model Numbers

- 3605-H321-V  
Shower-Hand Shower System with Symmons Temptrol® mixing valve p/n 4000-BODY and dual outlet diverter p/n 4-458E-BODY
- 3605-H321-V-TRM  
Trim only, valve and diverter ordered separately
- 4000-BODY  
Symmons Temptrol® mixing valve without trim
- 4000-X-BODY  
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service
- 4-458E-BODY  
Symmons dual outlet diverter valve without trim



## Finish Options / Modifications

*Append appropriate -suffix to model number*

- STN Satin Nickel
- Polished Chrome (standard finish)

## Options / Modifications

*Append appropriate -suffix to model number*

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve  
*(not available with -X integral service stops)*
- X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n 4000-X-BODY *(option only applies when ordering S-3605-H321-V)*
- CHKS Check Stops: Temptrol® mixing valve includes integral check stops  
*(Requires integral service stops, suffix -X. Used in installations where a positive shut-off device is used downstream of mixing valve.)*
- REV Reverse core: Temptrol® mixing valve with reverse core. *(Requires integral service stops, suffix -X. Used in back-to-back system installations. HOT on the right, COLD on the left)*
-  -2.0 2.0 gpm (7.6 L/min) flow rate restrictor
-  -1.5 1.5 gpm (5.7 L/min) flow rate restrictor
- LW Wide lever handle (chrome finish only)
- L/HS Hand shower wand not included  
*(includes hose, in-line vacuum breaker, wall connections and flange only)*
- L/HD Showerhead not included  
*(includes showerhead arm and flange only)*
- B48 48 inch slide bar in place of standard 30"
- 72 6 foot flexible metal hose in place of 5 foot
- R60 5 foot vinyl hose in place of flexible metal hose
- R72 6 foot vinyl hose in place of flexible metal hose
- QD Quick-disconnect at hand shower wall connection

## Standards / Certifications

ASME A112.18.1 / CSA B125.1

Americans with Disabilities Act (ADA) compliant

## Warranty

- 5 years - for commercial installations

# Dimensions Duro Shower-Hand Shower System, 3605-H321-V

