



SYMMONS[®] Symmetrix[®]
the smart choice[™]

Symmons Symmetrix[®] faucets are available for a wide variety of commercial and institutional applications.

Backed by the legendary Symmons name for quality, you can be assured you are specifying products that deliver the highest performance available in faucet technology, while meeting all known codes and standards.

Beneath the contemporary styling of every Symmons Symmetrix[®] faucet you'll find a heart machined of solid brass and copper. Built to withstand the abuse of time and guaranteed to provide flawless performance under the broadest range of water conditions, our full line of faucets feature the state-of-the-art Symmetrix ceramic control cartridge.



Symmons Symmetrix[®]
lavatory faucet is
available in this finish:



Polished
Chrome

Symmetrix[®] Lavatory Faucets

Widespread Lavatory Faucets



S-243-2-LAM

Two handle lavatory faucet with quarter-turn ceramic control components and lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-243-1-LAM Faucet with lift-rod only

S-243-LAM Faucet only



S-244-2-LAM

Two handle lavatory faucet with quarter-turn ceramic control components and lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-244-1-LAM Faucet with lift-rod only

S-244-LAM Faucet only



S-254-LWG

Two handle lavatory faucet with quarter-turn ceramic control components and wrist blade lever handles. 9-1/2" rigid/swivel gooseneck spout. Includes aerator. 1/2" IPS shanks, 8" to 16" centers.

Modifications: Suffix G: Grid drain in lieu of pop-up (S-244-2 only) • Suffix Delete LAM: Standard blade handles (chrome only) • Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix LAM: Metal finish insert handles • Suffix LPO: White insert handles • Suffix LWG: Wrist blade handles • Suffix NA: Non-aerated laminar flow outlet spray • Suffix OFG: Offset grid strainer • Suffix VP: Vandal resistant aerator

Centerset Lavatory Faucets



S-240-2-LAM

Two handle lavatory faucet with quarter-turn ceramic control components and blade handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-240-1-LAM Faucet with lift-rod only

S-240-LAM Faucet only



S-250-2

Two handle cast brass lavatory faucet with quarter-turn ceramic control components and blade style lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 4" centers.

S-250-1 Faucet with lift-rod only

S-250-0 Faucet without lift-rod hole

S-250 Faucet only



S-250-2-LWG

Two handle cast brass lavatory faucet with quarter-turn ceramic control components and wrist blade lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 4" centers.

S-250-1-LWG Faucet with lift-rod only

S-250-0-LWG Faucet without lift-rod hole

S-250-LWG Faucet only



S-20-2

Single handle lavatory faucet with ceramic control components and handle limit stop. Includes aerator, lift-rod with pop-up drain assembly. 3/8" supplies, 4" centers.

S-20-1 Faucet with lift-rod only

S-20-0 Faucet without lift-rod hole

S-20 Faucet only

S-20-2-G Faucet with grid strainer drain assembly

Modifications: Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix G: Grid drain in lieu of pop-up (S-240-2 only) • Suffix LAM: Metal finish insert handles • Suffix LPO: White insert handles • Suffix LWG: Wrist blade handles • Suffix NA: Non-aerated laminar flow outlet spray • Suffix OFG: Offset grid strainer (S-240-2 only) • Suffix VP: Vandal resistant aerator • Suffix BH: Braided hose supplies • Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix G: Grid drain in lieu of pop-up (S-240-2 only) • Suffix IPS: 1/2" IPS adaptors • Suffix LP: Loop handle • Suffix W: 6" lever handle (S-20-2 only)

Bar and Laundry Faucets



S-245-LAM

Two handle bar sink faucet with quarter-turn ceramic control components and lever handles. 3-1/2" x 9-1/8" swivel/rigid spout. Includes aerator. 1/2" IPS shanks, 4" centers.



S-245-5-LWG

Two handle bar sink faucet with quarter-turn ceramic control components and wrist blade lever handles. 5-1/2" x 12-3/16" swivel/rigid spout. Includes aerator. 1/2" IPS shanks, 4" centers.



S-249

Two handle laundry sink faucet with quarter-turn ceramic control components and blade handles. 7-5/8" x 7" 360 degree swing spout with hose thread. 1/2" IPS shanks, 4" centers.

Modifications: Suffix VP: Vandal resistant aerator • Suffix LAM: Metal insert lever handles (not available on S-249 series)

• Suffix LPO: White insert lever handles (not available on S-249 series) • Suffix LWG: Wrist blade lever handles (not available on S-249 series)





Symmons Industries, Inc., 31 Brooks Drive, Braintree, MA 02184-3804
Tel: 1-800-SYMMONS, (781) 848-2250 • Fax: 1-800-961-9621, (781) 664-1300
www.symmons.com

Copyright © 2009 Symmons Industries, Inc., Braintree, Massachusetts
0040-11/09