Location:



Hand Shower System 4703 Specification Submittal

Feature Highlights

- Symmons hand shower system with lever handles.
- Symmons Temptrol® pressure balancing mixing valve with adjustable stop screw to limit handle turn.
- Wall/hand shower, 3 mode, 5 foot flexible metal hose, in-line vacuum breaker, wall connection and cradle for hand shower mounting, #H303-V
- Standard flow rate 2.5 gpm (9.5 L/min)

☐ 4703Hand Shower System with

Polished chrome finish

Model Numbers

1	Symmons Temptrol® pressure balancing mixing valve p/n 4000-BODY
	Гrim only, valve must be ordered separately
1	Symmons Temptrol® pressure balancing mixing valve without trim
1 1 5	Symmons Temptrol® pressure balancing mixing valve without trim. Valve includes integral service stops to allow water shutoff for service

Finish Options / Modifications

Append appropriate -suffix to model number.

☐ -STN Satin nickel

- Polished chrome (standard finish)



Options / Modifications

Append appropriate -suffix to model number.

- □ -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- -X Symmons Temptrol[®] pressure balancing mixing valve includes integral service stops to allow water shut-off for service, p/n 4000-X-BODY. (Option only applies when ordering model 4703)
- □ -2.0 2.0 (7.6 L/min) flow rate restrictor
- ☐ -1.5 1.5 (5.7 L/min) flow rate restrictor
- -LAM Metal finish insert handle
- ☐ -LR Lever handle



Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime to the original end purchaser in consumer installations.
- 5 years for commercial installations





