Location:



Lavatory Faucet SLS-3512, SLS-3510 9 **Specification Submittal**



SLS-3510



Model Numbers

- ☐ SLS-3512 Lavatory Faucet with pop-up drain assembly (p/n LN-01296)
- ☐ SLS-3510 Lavatory Faucet only (p/n LN-01295)

Finish Options / Modifications

Append appropriate -suffix to model number.

- Polished chrome (standard finish)
- Satin nickel (premium finish)

Feature Highlights

- Single post round lavatory faucet with quarter turn ceramic control components
- Single swival lever handle with red & blue hot/cold indicators
- Single hole deck mounting
- 4 inch deck plate (optional)
- 20 inch braided supply hoses with 3/8 inch threaded compression connectors
- Pop-up drain and lift rod assembly (model SLS-3512)
- Aerator with 2.2 gpm flow rate (8.3 L/min) Optional aerator available in lower flow rates 🥢



- Metal construction
- Polished chrome finish (standard)

Options / Modifications

Append appropriate -suffix to model number.

- -1.0 1.0 (3.8 L/min) Flow rate restrictor
- -1.5 1.5 (7.6 L/min) Flow rate restrictor
- П
- -0.5 0.5 (1.9 L/min) Flow rate restrictor
- П

П

- -NA Non-aerated laminar flow outlet at 2.2 gpm (8.3 L/min)
- -DP4 4 inch deck plate
 - -STN Satin nickel finish

Standards / Certifications

ASME A112.18.1/CSA B125.1 NSF/ANSI 61.9; NSF/ANSI 372 WaterSense 1.5 gpm (5.7 L/min)





Section 116875 of the California Health and Safety Code

Warranty

- Limited Lifetime to the original end purchaser in consumer installations.
- 5 years for commercial installations

