

Diverter Valve Trim 57-2DIV-TRM **Ligature Resistant Specification Submittal**





Feature Highlights

- Dual Outlet Diverter Valve Trim with ligature resistant knob
- Trim is used with Symmons dual-port diverter valve
- Vandal resistant screws
- Metal construction
- Polished chrome finish (standard)

Model Numbers

☐ 57-2DIV-TRM Dual outlet diverter valve trim (diverter valve not included)

Finish Options / Modifications

Append appropriate -suffix to model number

- Polished Chrome (standard finish)

Disclaimers

- Product is designed to reduce likelihood that unit could be used as a device for hanging.
- Product is not a substitute for the evaluation, treatment or appropriate supervision of persons at risk of suicide

Warranty

- Limited Lifetime to the original end purchaser in consumer installations.
- 5 years for commercial installations

Standards / Certifications

ASME A112.18.1/CSA B125.1

Dimensions Lig-Res Diverter Valve Trim, 57-2DIV-TRM finished wall 3-1/2" Hole size: (89 mm) Ø 5-5/8" 3-1/2" (89 mm) max. (143 mm) 3" (76 mm) min. 3-7/8" (98 mm) max.* 2-3/4" (70 mm) min.3 All ports both (1) Dimensions identified with an asterisk (*) apply when diverter valve is installed without primary mixing control valve. 1/2" male IPS and 1/2" female sweat When diverter valve is coupled with a primary mixing control valve, then dimension is determined by rough-in drawing provided with mixing control valve. (2) Dimensions subject to change without notice