

Location:

# SYMMONS® Safetymix® Shower System 1-100 Specification Submittal



## Feature Highlights

- Symmons shower system with Symmons Safetymix pressure balancing mixing valve and lever style handle. Valve includes adjustable stop screw to limit handle turn.
- Super showerhead #4-231, single mode with adjustable flood or mist spray.
- Showerhead arm and flange.
- Standard flow rate 2.5 gpm (9.5 L/min)  
*Optional lower flow rate restrictor available*
- Polished chrome finish

## Model Numbers

- 1-100  
Shower System with Symmons Safetymix pressure balancing mixing valve

## Finish Options

*Append appropriate -suffix to model number.*

- Polished chrome finish (standard)

## Standards / Certifications

ASME A112.18.1/CSA B125.1



## Warranty

- Limited Lifetime - to the original end purchaser in residential/consumer installations.
- 5 years - for commercial installations

## Options / Modifications

*Append appropriate -suffix to model number.*

- CG** -1.5 1.5 gpm (5.7 L/min) flow restrictor
- 2.0 2.0 gpm (7.6 L/min) flow restrictor
- BX Back connection with integral stops
- E External volume control on showerhead
- G Dial thermometer
- NU NU-Arm head bracket in place of 300 arm and flange
- VP Vandal resistant escutcheon screws in place of standard screws
- X Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations
- X-3/4" 3/4" valve to increase flow approximately 20%
- X-CHKS Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve

## Dimensions *Safetymix Shower System, 1-100*

