KABLELITE

Kable Lite 4" Round Power Feed Canopy Dual-Feed





DESCRIPTION

A dual-feed canopy is mounted to a wall or ceiling adjacent to the Kable Lite run. It can be used anywhere in the run. It brings power to the Kable Lite run from a remote dual-feed transformer (sold separately). The lowvoltage leads from the remote transformer are connected to the canopy leads inside a standard 4" junction box. The four leads from the canopy are 24" long and can be cut and bent in the field. To drop the Kable Lite system farther down from the ceiling, add two pair of hardwire feeds (sold separately). Isolating connectors for bare cable are included to isolate power feeds from each other.

SYSTEM

Available for Kable Lite.

INSTALLATION

This product can mount to either a standard 4" square electrical box or an octagon electrical box (not included).

OTHER INFORMATION

Black and white finish have chrome feeds. For use with a dual-feed remote transformer (sold separately).

WEIGHT

0.8lb / 0.36kg

ORDERING INFORMATION

700KP4C424 LENGTH	FINISH	
24"	B BLACK C CHROME S SATIN NICKEL	

W WHITE



FIXTURE TYPE: JOB NAME: NOTES:	700KP4C4	24	
	FIXTURE TYPE:		
NOTES:	JOB NAME:		
	NOTES:		

www.techlighting.com



©2011 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.