

# IBISS Head LED

## ARCHITECTURAL HEAD



SINGLE FLOOD - EDGE LIT



DOUBLE FLOOD - EDGE LIT



SINGLE WALL WASH



DOUBLE WALL WASH

| SPECIFICATIONS     | SINGLE  | DOUBLE      |
|--------------------|---|-------------|
| Input voltage:     | 12 volts  | 12 volts    |
| Output:            | 617 lms   | 1056 lms    |
| Power consumption: | 15 watts*   | 26.7 watts* |
| Color temperature: | 2700K or 3000K  |             |
| CRI:               | 80  |             |
| Life:              | 50,000 hrs 70%  |             |
| Dimming:           | To 10% with low-voltage electronic or magnetic dimmer |             |
| Warranty:          | 5 years   |             |

\*Includes canopy power consumption

### DESCRIPTION

Constructed of die cast aluminum, the IBISS heads are designed to celebrate what's achievable with LED resulting in a form that would never be possible with traditional lamping.

### SYSTEM

Available for FreeJack, MonoRail and Wall Monorail. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack LED Connector (sold separately).

### FINISH

Satin Nickel and Antique Bronze.

### LAMP


Dedicated 10 watt or 20 watt LED assembly.

### POWER SUPPLY


Integrated LED driver. Dimmable with low-voltage electronic dimmer. To be used on a 12 volt Tech Lighting system or with a T~TRAK FJ connector.

# IBISS Head LED


## ARCHITECTURAL HEAD




SINGLE FLOOD



DOUBLE FLOOD



SINGLE WALL WASH



DOUBLE WALL WASH

## ORDERING INFORMATION

| 700 | SYSTEM | IBIS           | FORM  | STYLE | LAMP  | LENGTH (A) | FINISH |
|-----|--------|----------------|-------|-------|-------|------------|--------|
|     | FJ     | FREEJACK       | FE    | S     | L2    | 03 3"      | Z      |
|     | MO     | MONORAIL       |       | D     |       | 06 6"      | 5      |
|     | WMO    | WALL MONORAIL* | FS    |       | L3    | 12 12"     |        |
|     |        |                | WW    |       |       | 18 18"     |        |
| 700 | _____  | IBIS           | _____ | _____ | _____ | _____      | _____  |

\* FOR SINGLE HEAD, USE UP TO 12" MAXIMUM LENGTH, AND FOR DOUBLE HEAD USE UP TO 6" MAXIMUM LENGTH.

700 \_\_\_\_\_ IBIS \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

Tech Lighting

**LED lighting facts**  
A Program of the U.S. DOE

---

**Light Output (Lumens)** 617

**Watts** 15

**Lumens per Watt (Efficacy)** 41

---

**Color Accuracy** 81  
Color Rendering Index (CRI)

---

**Light Color** 3219 (Bright White)  
Correlated Color Temperature (CCT)

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008. Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YKL8-PV2412 (9/25/2012)  
Model Number: 700 FJ IBISFES L3065  
Type: Track light



**TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
Skokie, Illinois 60077 F 847.410.4500

[www.techlighting.com](http://www.techlighting.com)

## IBISS LED HEAD AWARDS

