Elton Head

DESCRIPTION

Adjustable double head tilts and rotates infinitely. Integral louver lens holders can hold a single glass lens (sold separately) or an eggcrate louver (two included). Two low-voltage, MR16 lamps of up to 35 watts each (not included).

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

WEIGHT

0.5lb / 0.23kg ±

ORDERING INFORMATION

| 700 SYSTEM ELT | LENGTH | FINISH |
|---|--|--|
| FJ FREEJACK MO MONORAIL MO2 TWO-CIRCUIT MONORAIL WMO WALL MONORAIL | 03 3" 06 6" 12 12" 18 18" 24 24" | Z ANTIQUE BRONZE C CHROME S SATIN NICKEL |
| | | |



| 700 E | LT |
|---------------|----|
| FIXTURE TYPE: | |
| JOB NAME: | |
| NOTES: | |
| | |
| | |

©2013 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.

