Sprocket Head

DESCRIPTION

Sleek Sprocket, with its removable handle, has many accessory options. Head rotates 360° and pivots 300° on vertical axis. Low-voltage, MR16 lamp of up to 75 watts (not included).


INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS

Backlight Shield, Barndoors, Flight Paper, Louver Lens Holder, Snap Louver Lens Holder, Spy Accessory

0.35-0.9lb / 0.16-0.41kg ±



ORDERING INFORMATION

700 SYSTEM SP	LENGTH	FINISH
FJ FREEJACK MO MONORAIL MO2 TWO-CIRCUIT MONORAIL WMO WALL MONORAIL	1 1" 3 3" 6 6" 12 12" 18 18" 24 24"	Z ANTIQUE BRONZE C CHROME S SATIN NICKEL



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

700 S	P
FIXTURE TYPE: JOB NAME:	
NOTES:	



©2013 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.