

# LOW-VOLTAGE HEADS

## Spot Head

### DESCRIPTION

Classic head rotates 360° around stem, pivots 290°. Can hold one lens or louver (sold separately). Low-voltage, MR16 lamp of up to 50 watts (not included).

### INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

### ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

### WEIGHT

0.84lb / 0.38kg ±



## ORDERING INFORMATION

700 SYSTEM	SPT6	LENGTH	FINISH
FJ	FREEJACK	04 4.5"	C CHROME
MO	MONORAIL	06 6"	S SATIN NICKEL
MO2	TWO-CIRCUIT MONORAIL	12 12"	
WMO	WALL MONORAIL	18 18"	



**TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 \_\_\_\_ SPT6 \_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



©2013 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.