

# INSTALLATION INSTRUCTIONS

Model # 72556-143C

READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

## PREPARING FOR INSTALLATION (Fig. 1)

1. Shut off the power at the circuit breaker and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.

## CONNECTING THE WIRES (Fig. 2)

3. While supporting the fixture, connect the electrical wires as shown in Fig. 2, making sure that all wire connectors (I) are secured. If your post has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding. After wires are connected, tuck them carefully inside the post cup (J).

## COMPLETING THE INSTALLATION (Fig. 1)

4. Unscrew the screw (F), separate the cover (A) from the fixture frame (K), then put the socket tube (D) to the socket (E).
5. **Install 60W/type B bulbs (bulbs not included) in accordance with the fixture specification. —DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
6. Place the glass (B) into the slot of the fixture frame (K) and secure with glass clip (C),
7. Fasten the fixture cover (A) to the fixture frame (K) with the screws (F).
8. Attach the post (H) to the post cup (J) with the set screws (G).

Your installation is now complete. Return power to the junction box and test the fixture

**IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.**

