INSTALLATION INSTRUCTIONS

Item#9161 (New. 05/10/2012)
READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE BACKPLATE (Fig.1)

- 1. Shut off the power at the circuit breaker and remove the old fixture and mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. Attach the crossbar (B) to the junction box (A) with Screws (C). The side of the crossbar marked "GND" must face out.
- 4. Thread the nipple (D) part way into the center hole of the crossbar (B).

CONNECTING THE WIRES (Fig. 2)

5. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the crossbar using the green screw provided. After the wires are connected carefully tuck them inside the junction box.

COMPLETING THE INSTALLATION

- 6. Align the backplate (H) and reflector (J) over the nipple (D) and secure with cap nut (F).
- 7. To prevent moisture from entering the outlet box and causing a short, use clear caulking (i.e. Indoor/Outdoor Silicone Sealant) to outline the outside of fixture back-plate where it meets the wall leaving a space at bottom to allow moisture a means to escape (Fig.3).
- 8. Install 1*60W T10 bulb (included) in accordance with the fixture's specifications (DON'T EXCEED THE MAXIMUM WATTAGE RATING!!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).
- 9. Loosen the metal clip (I) via screw (E) with wrench (G) and turn it to face the back of the fixture. Place the glass shade (K) into the metal frame of fixture body.
- Adjust the metal clip (I) to rest on the glass shade (K) and secure with screw (E) via wrench (G).

Your installation is now complete. Return the power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.







