



SPECIFICATIONS

Input Voltage.....	208-240VAC Single Phase
Kilowatt Rating.....	11.0
Maximum Amperage.....	55 AMPS
Breaker Size.....	60AMPS
Water Inlet.....	3/8" Compression
Steam Outlet.....	1/2" NPT
Drain Pan.....	3/4" NPT
Safety Valve.....	3/4" NPT
Electrical Connection.....	Hardwired
Maximum Room Size (Cubic Feet).....	395

FX Series Auto Flush Steam Generator

FX Series Auto Flush Series Standard Equipment:

- Auto PowerFlush – Pressurized inner tank cleaning system
- Includes Fast Start – Steam in seconds... not minutes
- Constant Steam at a constant rate
- Unit has 208-240 volt power connections to be installed by your licensed electrician
- Superior heating element – low watt density
- Includes Stainless Steel drain pan
- Can be plumbed up to 50 ft. from the steam room without upsizing the generator
- Stainless steel construction throughout
- Temp Sensor is built into controller

Installation Notes:

Generator must be installed by a licensed electrician. Install this generator according to the installation guide supplied. Follow all local plumbing and electrical codes. Unit must be accessible for service and maintenance. Generator is factory sized: L x W x H = Steam Room Cubic Feet = 395 Cu. Ft. max. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

Product Specification Basics:

The steam generator unit dimensions are approximately 18-3/4" L x 18-1/8"W x 12-3/4"H in dimension. The generator shall be made from stainless steel.

Shipping Information:

Weight..... 28 lbs.
 Length.....21 in.
 Width.....10.5 in.
 Height.....14 in.

For any further assistance please contact ThermaSol at 800.776.0711 or sales@thermasol.com

