



SPECIFICATIONS

| | |
|-------------------------------------|-------------------------|
| Input Voltage..... | 208-240VAC Single Phase |
| Kilowatt Rating..... | 8.0 |
| Maximum Amperage..... | 37 AMPS |
| Breaker Size..... | 40 AMPS |
| Water Inlet..... | 3/8" Compression |
| Steam Outlet..... | 1/2" NPT |
| Safety Valve..... | 3/4" NPT |
| Electrical Connection..... | Hardwired |
| Maximum Room Size (Cubic Feet)..... | 140 |

FX Series Manual Flush Steam Generator

FX Series Manual Flush Series Standard Equipment:

- Manually Operated PowerFlush – Pressurized inner tank cleaning system
- Includes Fast Start – Steam in seconds... not minutes
- Constant Steam at a constant rate
- Unit has 208-240 volt power connections to be installed by your licensed electrician
- Superior heating element – low watt density
- Can be plumbed up to 50 ft. from the steam room without upsizing the generator
- Stainless steel construction throughout
- Temp Sensor is built into controller

Installation Notes:

Generator must be installed by a licensed electrician.
 Install this generator according to the installation guide supplied. Follow all local plumbing and electrical codes. Unit must be accessible for service and maintenance. Generator is factory sized: L x W x H = Steam Room Cubic Feet = 140 Cu. Ft. max. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

Product Specification Basics:

The steam generator unit dimensions are approximately 17-3/4" L x 6-1/8" W x 12-3/4" H in dimension. The generator is made from stainless steel.

Shipping Information:

Weight..... 25 lbs.
 Length.....21 in.
 Width.....10.5 in.
 Height.....14 in.

For any further assistance please contact ThermaSol at
 800.776.0711 or sales@thermasol.com

