



**SPECIFICATIONS**

Input Voltage.....	208-240VAC Single Phase
Kilowatt Rating.....	8.0
Maximum Amperage.....	37 AMPS
Water Inlet.....	3/8" NPT
Steam Outlet.....	1/2" NPT
Safety Valve.....	3/4" NPT
Electrical Connection.....	NEMA 6-50P
 Maximum Room Size (cubic Feet).....	 140

**Steamshower AF – Standard Equipment:**

- Auto PowerFlush – pressurized inner tank cleaning system
- Lifetime factory Warranty
- 2 year in-home warranty prior to the lifetime warranty
- FastStart – steam in seconds... not minutes (patented)
- Constant steam at a constant rate
- Split tank enhances performance and life-span
- Can be plumbed 50 ft. from the shower
- Superior heating elements - low watt density
- Stainless steel construction
- 208-240 volt plug-in power cord (5 ft.)
- Water tight data link cable for control

**Installation Notes:**

Install this generator according to the supplied installation guide. Follow local plumbing and electrical codes. Unit must be accessible.

Generator is factory sized: L x W x H = Cubic Feet. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

**Compatible options:**

- Thermatouch Series
- Signatouch Series
- Microtouch Series
- Signature Control Series
- Easy Start Series
- Wellness Packages
- Digital Shower Packages
- Serenity Light and Music series



**Product Specification:**

The steam generator shall be approximately 18" x 13.75" x 12" in dimension. The generator shall be made from stainless steel and include: Fast Start, Auto PowerFlush, Split Tank, and use a 100% networked digital technology.

**Shipping Information:**

Weight.....37 lbs.  
Length.....22 in.  
Width.....18 in.  
Height.....14 in.



Product UPC Code

For any further assistance please contact ThermaSol at 800.776.0711 or [sales@thermasol.com](mailto:sales@thermasol.com)

Visit [www.thermasol.com](http://www.thermasol.com) for a complete product definition

