

HRG4808-BS

Thor Kitchen - 48 inch Professional Gas Range in Black Stainless Steel



FEATURES

- Black Porcelain Drip Pan for easy surface cleaning
- Heavy Duty Continuous Cast Iron Cooking Grates
- Automatic Re-Ignition Safety Feature
- Black Zinc Alloy Knobs with Blue LED Illuminating Lights

Push Button Light Control

30" Oven:

- 4.2 cu.ft oven capacity
- Infrared Broil Burner: High-end broiler radiates heat to sear your food and seal in the juices: 16,500 BTU
- U-shape bake burner at 22,000 BTU
- Blue oven interior
- Commercial Convection Fan circulates heat for even distribution
- Two Halogen Lights increase visibility for the oven interior

18" Oven:

- 2.5 cu.ft oven capacity
- 1 tube burner with 14,000 BTU
- One Halogen Light increases visibility for the oven interior
- Thermostatically Controlled to attain the right temperature

BURNER PERFORMANCE

Total Number of Range Top Burners	6 Burners
Front Right (Dual)	18,000 BTU
Front Left (Dual)	18,000 BTU
Front Middle (Single)	18,000 BTU
Rear Right (Single)	15,000 BTU
Rear Left (Single)	15,000 BTU
Rear Middle (Single)	15,000 BTU
Griddle Burner	15000 BTU
Infrared broil burner	16500 BTU
U-shape burner	22000 BTU

TECHNICAL DETAILS

Fuel Type	Natural Gas / LP Convertible
Electrical Requirements	120V
Circuit Breaker (A)	15 or 20 A
Frequency (Hz)	60 Hz

ACCESSORIES (NOT INCLUDED)

Liquid propane Gas Conversion Kit

WARRANTY

2 Year Warranty On Parts and Labor

UPC CODE

6926697023563

CONTAINER LOAD

54 PCS/40HQ

DIMENSION & WEIGHT

Product Dimension

Product width	29 .875"
Product height (from bottom to top of back splash)	38.5"
Product height (from bottom to top of side panel)	35.9"
Product depth (from back panel to bullnose include gasket)	27.5"
Product depth (from back panel to control board include gasket)	26.3"
Product depth (from back panel to side panel front include gasket)	24.4"
Depth of control panel (minimum)	1.69"
Depth of control panel (bullnose)	3.05"
Cast iron cooking grate (W x L)	22.83*10.63"
Adjustable legs	Recommend not to exceed 1"
Power plug length	56 1/4"

Required Cutout Size (W x D x H) (in)

48.18" x 26.6" x 38.5"