

TOTO®

MW6263046CEFG

Aimes® One-Piece Toilet, 1.28 GPF with WASHLET®+ S500e

FEATURES

- Concealed supply connection for seamless installation
- Tornado Flush® system, high-efficiency (1.28 GPF/4.8 LPF)
- CeFiONtect® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Premist of bowl before each use
- Universal Height
- Elongated front bowl and WASHLET+ S500e
- 12" Rough-in
- Chrome plated trip lever
- Remote control operated

MODELS

- **MW6263046CEFG (#01)**
With CeFiONtect ceramic glaze & WASHLET S500e with contemporary design

COMPONENTS

- **CST626CEFGT40**
Elongated toilet with CeFiONtect
- **SW3046T40**
WASHLET® S500e with contemporary design

Optional Components

- **TSU03W.10R**
10" Unifit Rough-In
- **TSU03W.14R**
14" Unifit Rough-In

COLORS/FINISHES

- #01 Cotton

PRODUCT SPECIFICATION

The one-piece high-efficiency Tornado Flush system toilet shall be 1.28 GPF/4.8 LPF. Toilet shall be 12" Unifit rough-in. Toilet shall have optional CeFiONtect ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with Polished Chrome trip lever. Toilet shall be TOTO Model MW6263046CEFG#01

See SW3046T40 Specification Sheet for details on included WASHLET.



 **Tornado Flush**

 **ewater+**

 **CeFiONtect**

 **Skirted Design**

CODES/STANDARDS

- Meets or exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)



MW6263046CEFG


Aimes® One-Piece Toilet, 1.28 GPF with WASHLET®+ S500e

SPECIFICATIONS

Water Use	1.28 GPF (4.8 LPF)
Flush System	Tornado Flush®
Min. Water Pressure	8 psi (Flowing)
Water Surface	7-3/4" x 9-3/8"
Trap Diameter	2-1/8"
Rough-in	12" (10" & 14" Optional)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	119 lbs
Shipping Dimensions	32" L x 20" W x 17-3/4" H ¹ x 28-3/4" H ²


INSTALLATION NOTES

Back-to-Back Toilet Installations: TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS



TOTO®

These dimensions and specifications are subject to change without notice

Ph: (888) 295-8134 | Fax: (800) 699-4889 | www.totousa.com | © TOTO USA

SS-01328 v.01