CST744EF (R) N.10

Eco Drake® Transitional, 1.28GPF, 10" Rough-In

FEATURES

- Transitional design
- E-Max® flushing system, low consumption (1.28GPF/4.8LPF)
- Universal Height
- Two-piece design with high-profile tank
- Elongated front bowl and tank set, less seat
- ADA compliant
- Chrome trip lever
- 10" Rough-in, less supply

MODELS

- CST744EFN.10#01 Elongated bowl, 10" rough-in, less seat
- CST744EFRN.10#01
 Same as above with right hand trip lever

COMPONENTS

- C744EF.10 Elongated Front Bowl, 10" rough-in
- ST744E Tank and Cover only Left-hand trip lever
- ST744ER Tank and Cover only Right-hand trip lever
- SS114 SoftClose® seat (sold separately)
- SC134 commercial seat (sold separately)
- SC534 commercial seat (sold separately)

COLORS/FINISHES

Standard #01 Cotton

PRODUCT SPECIFICATION

The two-piece low consumption E-Max flushing system toilet shall be 1.28GPF/4.8LPF. Toilet shall be at universal height and be ADA compliant. Toilet shall have high-profile tank, elongated front bowl and Chrome trip lever. Toilet shall be TOTO Model CST744EFN #01.





CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)







Eco Drake® Toilet Transitional, 1.28GPF

SPECIFICATIONS

1.28 GPF/4.8LPF Water Use

Flush System E-Max Min. Water Pressure 8 psi (static) Water Surface 7-7/8" x 10-5/16"

Trap Diameter 2-1/8" Rough-in 10" Trap Seal 2-3/8"

Warranty One Year Limited Warranty

Material Vitreous china

Shipping Weight C744EF.10 48 lbs. ST744E(R) 36 lbs.

Shipping Dimensions C744EF.10

29" L x 15" W1 x 10-1/2" W2 x 17-1/8" H

ST744E(R) 20-3/4" L x 9" W x 18-1/8" H

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



