

# INSTALLATION INSTRUCTIONS

## TRADE-WIND® 10" ROOF CAP

#### PERFORMANCE · QUALITY · CUSTOMER SERVICE

REVISED: JANUARY 1, 2023

MODEL	DIAMETER	HEIGHT
HVRC10	9 ¾"	18"

ITEM #: 3BL-35-485RC



## **READ AND SAVE THESE INSTRUCTIONS**


Before beginning installation, please thoroughly read and become familiar with these instructions. Installation and service must be completed by a qualified installer. Failure to properly install this product may void the warranty. Always observe local building codes.

#### **DESCRIPTION:**

Trade-Wind® Roof Cap is designed to be installed as a termination of a 10" round duct run from either a Trade-Wind® indoor ventilation product or our outdoor BBQ Hood or BBQ Liner.

### **INSTALLATION DETAILS:**

The Roof Cap has a 9 3/4" round duct collar for attaching duct to the roof cap. Be sure and secure duct to roof cap collar using 3 or 4 equally spaced sheet metal screws along with the metal foil duct tape. Use roofing industry standard procedures for attaching roof cap flashing to sub roof material and weather proofing. Trade-Wind highly recommends installation of the roof cap by a roofing professional to insure proper installation.



For more information, please contact your dealer or your TRADE-WIND® representative.

8 0 0 WEST GRANT STREET
PHOENIX, AZ 8 5 0 0 7
1 - 8 0 0 - 9 5 5 - 5 7 3 7
6 0 2 - 9 0 0 - 8 5 0 0

T-WUSA.COM