

POSTMOUNT

AssemblyInstructions

MODEL#:40384



CAUTION

•Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

•Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape



Phillips screwdriver




Flat blade screwdriver




Pliers



Wire strippers



Fixture



Glass



Mounting Screws




Wire Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE

POSTMOUNT AssemblyInstructions MODEL#:40384


STEP 1

Unscrew the fixture top from fixture



STEP 2

1. Install bulb (Not Included) E26 Type A 60W
2. Put the glass into fixture carefully, and secure the fixture top onto fixture by cap nuts



STEP 3



Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor



STEP 4

Install the fixture to the pole or base (Not included) and secure with the pre-assembled screws

