

HANGING LANTERN

Assembly Instructions

Model#: 40385/40386



CAUTION

• Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

• Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape



Phillips screw driver



Flat blade screw driver



Pliers



Wire strippers




Fixture



Glass



Mounting Unit



Mounting Screws



Wire Nuts



Cap Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE


HANGING LANTERN

Assembly Instructions

Model#: 40385/40386


STEP 1

Unscrew the cap nuts and put down the metal shade from fixture




STEP 2

Put the glass into metal shade carefully, and secure the metal shade to fixture by cap nuts



STEP 3

Use the mounting screws to attach the mounting unit to the junction box.



Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the pre-installed green ground screw. Then, connect the positive, negative, and ground wires with the supplied wire nuts. Secure with electrical tape.

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor.

