

FLUSHMOUNT
Assembly Instructions

MODEL#: 16232 AG



CAUTION

- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning of the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape



Phillips screwdriver




Flat blade screwdriver




Pliers



Wire strippers



Fixture



Glass shade



Tube W / Threaded Pipe




Washer



Metal Pad



Finial



Mounting Screws



Wire Nuts

***PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**

FLUSHMOUNT
Assembly Instructions

MODEL#: 16232 AG

STEP 1
Screw the tube with the threaded pipe head into the coupling until tightened.

STEP 3
Use the mounting screws to attach the Fixture to the junction box until tightened.

STEP 2
Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape.

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor

STEP 4
Install bulbs (not included).E26 Max Watt 60W .
Place the fixture and glass shade over the mounting unit and secure the assembly with the finial.