72052
Assembly Instructions

CAUTION

- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED


Ladder


Safety glasses



Electrical tape


Phillips screwdriver



Flat blade screwdriver


Pliers



Wire strippers


Fixture*1


Glass shade*2


Mounting Unit*1


Mounting Screw*2


Wire Nut*3


Cap Nut*2



Socket Ring*2

***PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**

72052
Assembly Instructions


STEP 1


Use the mounting screws to attach the mounting unit to the junction box.




STEP 2

Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit, using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts . Secure with electrical tape.





Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:	Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:
Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.	White Supply Wire or Insulated Wire (other than green) with silver conductor



STEP 3

Place the fixture over the mounting unit and secure with the cap nuts.
Unsecure the preinstalled socket ring from the socket, then secure the shade to the socket cup using the socket ring.

Install E26*2*60W MAX bulb (not inc).

