

72057-3

Assembly Instructions



CAUTION

- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape



Phillips screwdriver




Flat blade screwdriver




Pliers



Wire strippers



Fixture*1



Glass Shade*1



Mounting Unit*1



Mounting Screw*2



Wire Nut*3



cap nuts*2

***PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**


72057-3

Assembly Instructions

STEP 1

Attach the mounting unit to the junction box (not included) with mounting screws.

Install the support screws to the mounting unit.



STEP 2

Make the electrical connection from the junction box to the fixture.

Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts .


Secure with electrical tape.

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor



STEP 3

Secure the fixture to the junction box by placing it over the preinstalled support screws on the mounting unit and secure with the cap nuts.

Secure the glass shade to the fixture.

Install three 60-watt max. medium-base incandescent bulbs(not included).

