UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com





Model:

TUC-48F-HC

Undercounter:


Solid Door Freezer with Hydrocarbon Refrigerant




TUC-48F-HC

- True's undercounter units are designed with enduring quality that protects your long term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- ▶ Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Oversized, environmentally friendly forced-air refrigeration system holds -10°F (-23.3°C). Ideally suited for both frozen foods and ice cream.
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back
- Interior attractive, NSF approved, clear coated aluminum liner with stainless steel floor.
- ▶ Heavy duty PVC coated wire shelves.
- Automatic defrost system time-initiated, time-terminated.
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

PLAN VIEW





ROUGH-IN DATA

Voltage: 220-240V/50Hz

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next $\frac{1}{2}$ ").

| . J. Lagar | | | | | | | | | | | | |
|------------|----------------|-------|---------|------|-----------------------|--------|---------------------------|-----|------|--|--|--------------------------|
| Model | Model Type | Doors | Shelves | | et Dime (mm) D† | nsions | Net Volume (litres) | EEC | EEI | 24 hr/ Energy Consumption (kWh) | Annual Energy Consumption (kWh) | Crated Weight (kg) |
| TUC-48F-HC | Counter Frozen | 2 | 4 | 1229 | 766 | 839 | 278 | D | 50.8 | 5.577 | 2036 | 132 |

[†] Depth does not include 26 mm for rear bumpers.

Test Standard: EN16825 - Climate Class 4 (30°C, 55% relative humidity).