











Stainless Frame

Stainless Solid

Integrated Frame

Integrated Solid

# **Additional Options**

Accessory panels are designed for easy installation on Integrated models



Stainless Handleless Panel

# **Key Features**

- Industry Exclusive: Full-depth lower interior maximizes storage options
- Industry Leading: Variable speed compressor delivers maximum energy efficiency, faster temperature response, and quieter operation
- Stainless steel interior
- Stainless steel cabinet, toe kick, and accents
- U-Adjust™ Interior: 19 adjustable positions
- Three removable, full-extension Slide & Secure™ Bins
- Convection cooling system provides a quick cool down and consistent temperature
- Temperature range: 33°F 70°F

- Adjustable bright white or blue LED lighting
- Soft close door with articulating hinge
- Volume of 5.2 cu ft holds up to 94 bottles (12 oz) or 148 cans (12 oz)
- Digital touch pad control with blue LED display
- Stainless steel handle (7/8" diameter)
- Integrated model requires 3/4" custom door panel and handle (not supplied by U-Line)
- Field reversible door is shipped right-hand hinged
- Built-in or freestanding
- Four adjustable leveling legs

### **MODEL DETAILS**


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHRE524-SG01A	115 / 60	Field Reversible	Stainless Frame	163 lb
UHRE524-SS01A	115 / 60	Field Reversible	Stainless Solid	148 lb
UHRE524-IG01A	115 / 60	Field Reversible	Integrated Frame	156 lb
UHRE524-IS01A	115 / 60	Field Reversible	Integrated Solid	139 lb

#### **ACCESSORIES**


Model	Description	Finish	Shipping Weight
ULAGRILLE24	Adjustable Grille (Accepts Integrated Panel)	Black	3 lb
ULASHP24FRAME*	Stainless Handleless Panel Frame	Stainless	10 lb
ULASHP24SOLID*	Stainless Handleless Panel Solid	Stainless	15 lb

<sup>\*</sup>Installs on integrated models.

#### **Front**




# \*Add $\frac{1}{2}$ " for Integrated models with 3/4" integrated panel installed. Side 22 15/16" 24 <sup>13</sup>/16" (583 mm)\* (630 mm) 24 1/4" (616 mm) 17 1/2" (445 mm) -4 ¾" (111 mm)




# **Specifications**

Model	HRE524
Amps: Running	1.2
Capacity: Bottle (12 oz)	94
Capacity: Can (12 oz)	148
Capacity: Volume (cu ft)	5.2
Capacity: Wine Bottle (750 ml)	N/A
Dimensions: Product Depth	22 <sup>15</sup> / <sub>16</sub> " / 583 mm
Dimensions: Product Height (Min.)	33 <sup>11</sup> / <sub>16</sub> " / 855 mm
Dimensions: Product Width	23 <sup>5</sup> /8" / 600 mm
Energy Consumption: Avg. Per Year	275 - 305 kWh
ENERGY STAR (glass door)	No
ENERGY STAR (solid door)	Yes
Product Weight: Max	163 lb
Refrigerant Type:	R600a
Sabbath (Star K Certified)	Yes
Temperature Range	33°F - 70°F



## **Cabinet Cut-Out**

**Back** 



# Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- 2 Year (parts & labor) / 5 year sealed system (parts) upgrade at no cost with product



registration

See complete warranty for details

#### **Installation Notes**

- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow







