

ASSEMBLY AND INSTALLATION

INSTRUCTIONS

22250

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. Thread the Mounting screws into the matching holes of the Circular strap, and tighten with the Hex nut. Thread the Ground screw into the hole of the Circular strap. Secure the Circular strap to the outlet box with the Outlet box screws.
3. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Circular Strap with the green Ground Screw.Carefully tuck wires back into the Outlet Box.
4. Place the fixture Canopy over the two Mounting screws so they protrude through the holes in the Canopy. Thread the Ball nut onto the Mounting screws and continue turning until the Fixture is snug against the wall.
5. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
6. Thread the Hex nut-1 onto the nipple, place the Cup and secure to the coupling. Slide the Tube, Cup-1, Metal washer, Plastic washer, Glass shade, Flat cap onto the nipple, secure with the Hex nut-2 and finial.
7. Turn on the power at fuse or Circuit Box.

