

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

CH25506

**WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.**

**NOTE: Before installing, consult local electrical codes for wiring and grounding requirements.**

1. Attach two screws to the mounting strap, then secure them with two lock nuts. Adjust the length of the screws if necessary.
2. Attach the mounting strap to the outlet box by using two mounting screws.
3. Screw nipple(-a) into coupling(-a), then secure it with a hex nut.
4. Attach the tube, twist core and cap(-a) onto nipple(-a), then secure them with the loop.
5. Choose the length of the chain you need, then weave the fixture wire and the fixture grounding wire through the chain. Then connect one end link of the chain with the loop by using the loop lock.
6. Connect the other end of the chain link to the top loop by using the loop lock.
7. Thread the fixture wire and the fixture grounding wire through the top loop, canopy and mounting strap.
8. Pull out the outlet wires and the house grounding wire from the outlet box. Make wire connections using the wire nuts:
  - The smooth wire (marked) from the fixture to the black wire from the power source.
  - The ridged wire (unmarked) from the fixture to the white wire from the power source.
  - Attach the fixture grounding wire to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with a wire nut.
 Carefully tuck the wires back into the outlet box.
9. Attach the canopy to the mounting strap by inserting two screws, then secure it with two bolt nuts.
10. Screw nipple(-b) into coupling(-b), then secure it with a hex nut.
11. Install bulbs for center light (not included). See relamping label at socket area or packaging for maximum allowed wattage.
12. Attach the center glass, rubber pad, cap(-b) and metal frame onto nipple(-b), then secure them with the finial.
13. Install bulbs for side light (not included). See relamping label at socket area or packaging for maximum allowed wattage.
14. Fix the glass shades to the fitters by threading the set screws onto the glass notches.
15. Turn on the power at the main fuse or circuit breaker box.

