# ASSEMBLY AND INSTALLATION INSTRUCTIONS

C0068

> **WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.**

NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. READ AND SAVE THESE INSTRUCTIONS.

Parts:

Parts Number (4943MM)

Mounting Strap (A)

Mounting Screw (B)

Green Grounding Screw (C)

Nipple (D)

Wire Nut (E)

Hex Nut (F)

Washer (G)

Finial (H)

Outlet Box
House Grounding Wire
Hex Nut (F)
Washer (G)
Mounting Strap (A)
Green Grounding Screw (C)
Mounting Screw (B)
Nipple (D)
Wire Nut (E)
Fixture Wire
Fixture Grounding Wire
Finial (H)
Fixture

Bulb Type B Max.60W (not included)

1. Attach the nipple to the mounting strap, then secure it with a washer and hex nut.
2. Attach the mounting strap to the outlet box by using two mounting screws.
3. Pull out the outlet wires and the house grounding wire from the outlet box. Make wire connections by using the wire nuts:
   - ---Connect the black wire from the fixture to the black wire from the power source.
   - ---Connect the white wire from the fixture to the white wire from the power source.
   - ---Attach the fixture grounding wire to the mounting plate with the green grounding screw. Then connect it to the house grounding wire with a wire nut.
   Carefully put the wires back into the outlet box.
4. Attach the fixture to the mounting strap by inserting the nipple, then secure it with a finial.
5. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.
6. Turn on the power at the main fuse or circuit breaker box.

VAXCEL

140106

A: 15"

B: 8-1/2"

VAXCEL