

ASSEMBLY INSTRUCTIONS

Hall Medium hanging Lantern Item # S 5793

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING * SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

- Carefully remove all parts from the carton.
- Insert light bulbs (not included) into sockets.
- Remove metal tabs (M) by removing screws (L), install glass panels (K) to each frame of lantern box (J) and secure with metal tabs (M) and screws (L).
- Feed the wires through the connection rod (H), connector (G) and connection rod (F).
- Hook connection rod (H) to top loop (I).
- Screw connector (G) onto the top nipple of connection rod (H) by turning in a clockwise direction until tight.
- Thread the bottom nipple of connection rod (F) into the connector (G) by turning in a clockwise direction until tight.
- Unscrew canopy collar (E), slide canopy collar (E) and canopy (D) on connection rod (F).
- Attach mounting strap (A) to ceiling outlet and secure with mounting screws (C) provided.
- Hook connection rod (F) to mounting loop (B).
- Attach the bare copper ground wire from the fixture to the ground junction box wire (usually green or copper), fasten together with a plastic wire connector. Tightly wrap the wire connector with electrical tape. Be sure no wire strands are exposed. **IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.**
- Connect neutral wire from fixture (ridged, molded wire) to the neutral wire from the junction box (usually white). Fasten both wires together with a plastic wire connector and tightly wrap the wire connector with electrical tape. Be sure no wire strands are exposed.
- Connect the hot wire from the fixture (smooth wire) to the hot wire (usually black) from the junction box. Fasten both together with a plastic wire connector and wrap the connection with electrical tape. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.**
- Tuck the wire connections neatly into the ceiling outlet box.
- Slip canopy (D) to the affixed mounting strap (A) and secure with canopy collar (E).
- Restore power and test fixture. Installation is complete.

*** Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents.

